

CERTIFICATE OF CONFORMITY

Product Listing Scheme: Scheme Type 5

| er/UEN: | 31 Ubi Ro #07-01 Singapor | e 408694 | Asia) r le | | | |
|---|---|---|--|---|---|--|
| Controlled Door Closing Device (Concealed Door Closer) | | | | | | |
| BRITON | | | | | | |
| C3024 | | | | | | |
| China | | | | | | |
| Cam action concealed door closer with back check function using sliding arm Only power size 3 to 4 can be used on fire rated doors Suitable for use on 240mins uninsulated fire rated doors Classification of Coding System: 3 8 4 1 1 0 See COC Appendix (1 page) for more details | | | | | | |
| SS 332:20 | 018 Clause | e 6 (Annex | C) | | | |
| Intertek No. 190121011SHF-BP-2 Sirim No. 2022FE0249 | | | | | | |
| _ | ance with S | SCDF Fire (| Accr Certi SAC Body | edited fication | ents. | |
| | (Conceale BRITON C3024 China Cam actic Only pow Suitable f Classifica 3 See COC SS 332:20 Intertek N Sirim No. | #07-01 Singapor er/UEN: 20000712 Controlled Door Clos (Concealed Door Clos (Concealed Door Clos BRITON C3024 China Cam action conceale Only power size 3 to Suitable for use on 2 Classification of Coor 3 8 See COC Appendix SS 332:2018 Clause Intertek No. 1901210 Sirim No. 2022FE02 d in accordance with S | Singapore 408694 er/UEN: 200007123E Controlled Door Closing Device (Concealed Door Closer) BRITON C3024 China Cam action concealed door clos Only power size 3 to 4 can be u Suitable for use on 240mins un Classification of Coding System 3 8 4 2 See COC Appendix (1 page) fo SS 332:2018 Clause 6 (Annex 4 Intertek No. 190121011SHF-BF Sirim No. 2022FE0249 d in accordance with SCDF Fire 0 | #07-01 Singapore 408694 er/UEN: 200007123E Controlled Door Closing Device (Concealed Door Closer) BRITON C3024 China Cam action concealed door closer with ba Only power size 3 to 4 can be used on fir Suitable for use on 240mins uninsulated Classification of Coding System: 3 8 4 2 1 See COC Appendix (1 page) for more de SS 332:2018 Clause 6 (Annex C) Intertek No. 190121011SHF-BP-2 Sirim No. 2022FE0249 d in accordance with SCDF Fire Code 2013 | #07-01 Singapore 408694 er/UEN: 200007123E Controlled Door Closing Device (Concealed Door Closer) BRITON C3024 China Cam action concealed door closer with back check f Only power size 3 to 4 can be used on fire rated door Suitable for use on 240mins uninsulated fire rated door Suitable for use on 240mins uni | #07-01 Singapore 408694 er/UEN: 200007123E Controlled Door Closing Device (Concealed Door Closer) BRITON C3024 China Cam action concealed door closer with back check function us Only power size 3 to 4 can be used on fire rated doors Suitable for use on 240mins uninsulated fire rated doors Classification of Coding System: 3 8 4 1 1 0 See COC Appendix (1 page) for more details SS 332:2018 Clause 6 (Annex C) Intertek No. 190121011SHF-BP-2 Sirim No. 2022FE0249 d in accordance with SCDF Fire Code 2018 requirements. |

Certificate No. Date of Original Issue No. o 20A0369 12 January 2021

No. of Page(s) 1 of 2

Date of Last Revision 13 July 2022 Date of Expiry 11 January 2026

This Certificate is part of a full report and should be read in conjunction with it. This Certificate remains the property of Singapore Test Services Pte Ltd ("STS") and shall be returned upon request. The use of this Certificate is subjected to the terms and conditions of the Product Listing Scheme of STS. The above certified company is solely responsible for compliance of any product that has the same designation as the product type tested. Parties relying on this Certificate should verify its validity with STS.



APPENDIX

Product Details: Cam action concealed door closer with back check function using sliding arm Classification of coding system for concealed door closer as per below

| <u>1st Digit</u> Category of Use | 2nd Digit Test Duration | <u>3rd Digit</u> Door Closer Power Size | <u>4th Digit</u> Fire Resistance | <u>5th Digit</u> Essential requirements of safety use | <u>6th Digit</u> Corrosion Resistance |
|--|----------------------------|--|--|---|--|
| 3 | 8 | 4 2 | 1 | 1 | 0 |
| Grade 3 For closing door from 105° | 500,000 cycles | (Only power size 3 to 4 can be used on fire rated doors) | <u>Grade 1</u> *Suitable for 240mins uninsulated fire rated doors. | Grade 1 Satisfied essential requirements of safety use | Grade 0 no defined corrosion resistance |

*Please refer to Sirim No. 2022FE0249.

Head of Certification

Certificate No.Date of Original IssueNo. of Page(s)Date of Last Revision20A036912 January 20212 of 213 July 2022

Date of Expiry 11 January 2026

This Certificate is part of a full report and should be read in conjunction with it. This Certificate remains the property of Singapore Test Services Pte Ltd ("STS") and shall be returned upon request. The use of this Certificate is subjected to the terms and conditions of the Product Listing Scheme of STS. The above certified company is solely responsible for compliance of any product that has the same designation as the product type tested. Parties relying on this Certificate should verify its validity with STS.